


S-TRACK 3-phase surface-mounted track

240V track, black, 3 m

Aluminium bearing track of the 240V 3-phase surface-mounted track system. Installation can be done through the existing holes in the profile directly onto the wall or the ceiling. The surface-mounted version of this system is available in several colours and lengths. Alternatively, there is a recessed version available too.



TECHNICAL DATA

Item no.:	175030
Nominal voltage	220-250V ~50Hz V
Length	299.5 cm
Width	3.6 cm
Height	3.6 cm
Net weight	2.638 kg
Gross weight	3.332 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Color	black

							4				4			4		4		4	4	4	4	ч	4	4	4	4	4									
	4	- 4		J	J.	J	J	J	J	J.	J	J	J	J	J,	a,	ä	a,	a,																	
J	ı J	ר ר	1	J	1	J	J	J.	J	1	J	J.	J	J	ä	J	ä		a,			J		J.		ı	J.	J	J.	J	J.	. د	١,	1	ı	ı,
					4					1		1	4	-1	1	1	а.	1	1	1	1	1	1	1	1	т.	4	4								



Accessories

1002845	Steel wire suspension for EUTRAC® , S-TRACK and 1 phase tracks, 5m, set of two
---------	--

Notes			