## а. л. - **1** . ы н ы . . ........... л ГГ Л . . . . . . . . . . . а. \_\_\_ . . . . . . . . . . . . . . . . . . L






## **ASSO 300**

## wall light, LED, 2000K-3000K Dim to Warm, brushed aluminium/white

The distinctive LED UP/DOWN recessed wall light ASSO 300 is equipped with two ultra-modern, powerful COB LEDs which emit light indirectly. Thus it is ideal for glare-free lighting of stairs, staircases and rooms. The lighting atmosphere can be adjusted/dimmed in an uncomplicated way using the dim-to-warm function. Due to the incorporated constant current LED driver, placed within the canopy, the electrical connection is made directly to 230V mains supply. This luminaire contains built-in LED lamps.



## **TECHNICAL DATA**

Item no.:	1000635
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Width	30.0 cm
Height	7.0 cm
Depth	9.5 cm
Net weight	1.088 kg
Gross weight	1.343 kg
IP Code	IP 20
Safety class	1
Assembly	Surface
Assembly details	Wall
Dimming technology	Leading edge
Wattage	22 W
Lumen	1380 lm
Colour temperature	2000-3000 Kelvin
Color	aluminium
CRI	>90
Binning	6
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	223

Notes