


## **LOGS IN L**

## Indoor LED recessed wall light, alu/white, 2000-3000K, DIM-TO-WARM

The distinctive LED UP/DOWN recessed wall light LOGS IN L is equipped with an ultra-modern, powerful LED which emits its controllable, warm white light indirectly. It is therefore excellent for glare-free lighting of stairs, staircases and rooms. The LOGS IN L has infinitely variable and completely flicker-free dimming due to the dim-to-warm function. Due to the operating device incorporated in the canopy, the electrical connection is made directly to the 230V mains power supply.



## **TECHNICAL DATA**

| Item no.:                           | 1002930                |  |  |
|-------------------------------------|------------------------|--|--|
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |  |  |
| Secondary power / secondary voltage | 500 mA/V               |  |  |
| Length                              | 30.0 cm                |  |  |
| Height                              | 7.0 cm                 |  |  |
| Depth                               | 10.0 cm                |  |  |
| Net weight                          | 1.34 kg                |  |  |
| Gross weight                        | 1.564 kg               |  |  |
| IP Code                             | IP 20                  |  |  |
| Safety class                        | I                      |  |  |
| Assembly                            | Surface                |  |  |
| Assembly details                    | Wall                   |  |  |
| Dimming technology                  | Leading edge           |  |  |
| Wattage                             | 19 W                   |  |  |
| Lumen                               | 1500 lm                |  |  |
| Colour temperature                  | 2000-3000 Kelvin       |  |  |
| Color                               | aluminium              |  |  |
| CRI                                 | >90                    |  |  |
| Binning                             | 3                      |  |  |
| LXXBXX data                         | 70/50                  |  |  |
| Service life                        | 30000 h                |  |  |
| Maximum ambient temperature         | 40 °C                  |  |  |
|                                     | <del>,</del>           |  |  |





| BIG WHITE Page | 213 |
|----------------|-----|
|----------------|-----|