





VANO WING

outdoor floodlight, LED, 3000K, silver-grey, W/H/D 63.5/6.5/20.5 cm

Single-headed luminaire of the VANO series made from aluminium for area or display and advertising board illumination. The dimmable VANO WING LED is suitable for wall, ground and ceiling mounting. Thanks to the integrated asymmetrical reflector, an even and wide-area lighting is possible even at small separation distances to the illuminated surface. Thanks to the built-in LED driver, the luminaire can be connected directly to the 230V mains supply. With protection class IP65 it is suitable for outdoor use. The assembly holders make assembly easier.





TECHNICAL DATA

Item no.:	227734		
Lamps included	0		
Number of different light outlets	1		
Primary nominal voltage	120-277V ~50/60Hz mA/V		
Secondary power / secondary voltage	525 mA/V		
Vertical tilting range	180 °		
Width	63.5 cm		
Height	6.5 cm		
Depth	20.5 cm		
Net weight	3.581 kg		
Gross weight	4.081 kg		
IP Code	IP 65		
Safety class	I		
Impact resistance class	IK02		
Impact resistance	0,20000000000000001 Joule		
Assembly	Surface		
Assembly details	Ceiling, Ground, Wall		
Dimming technology	1-10V		
Wattage	25 W		
Lumen	1500 lm		
Colour temperature	3000 Kelvin		
Beam angle	120 °		





Color	grey
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	635

Notes			