## а. л Л . л. ы ..... л л L ы . . . . . . . . . . . гг гг \_\_\_ . . . . . . . . . . . . . . . . . . л







## OUT BEAM

## outdoor wall light, LED, 3000K, beam up/flood down, silver-grey, IP44

The OUT BEAM series LED wall light, available in single-headed and double-headed versions, was designed especially as an architectural accent illumination. The LED light sources lie opposite each other and are covered by glass, they produce a narrow and a wide beam respectively and thus create the special up/down effect. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use. The electrical connection of the luminaire is made directly to the 230V mains supply thanks to the built-in LED driver. The OUT BEAM series also includes wall lights for halogen lamps.





## **TECHNICAL DATA**

Item no.:	229664
Lamps included	0
Number of different light outlets	2
Primary nominal voltage	120-277V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Width	15.0 cm
Height	15.0 cm
Depth	15.8 cm
Net weight	1.539 kg
Gross weight	1.751 kg
IP Code	IP 44
Safety class	1
Assembly	Surface
Assembly details	Wall
Wattage	18 W
Lumen	740 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	grey
CRI	>80
Binning	6
Binning 2	6



LXXBXX data	70/50
Service life	25000 h
Service life 2	25000 h
BIG WHITE Page	699

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes