



## **LOGS WALL**

outdoor wall light, LED, 3000K, IP44, square, anthracite, 8W

The indirect LED wall luminaire LOGS WALL is made from aluminium and equipped with a high-performance planar LED. Depending on the version various housing colours are available. The required driver for direct connection to 230V mains supply is included in each package. In addition, the installation can be extended by floor lamps of the series.





## **TECHNICAL DATA**

Secondary power / secondary oltage 500	0-240V ~50/60Hz mA/V 0 mA/V 0 cm cm 2 cm
Primary nominal voltage 100 Secondary power / secondary oltage 500 Vidth 13.0	0 mA/V 0 cm cm 2 cm
Secondary power / secondary oltage 500	0 mA/V 0 cm cm 2 cm
Vidth 13.0	0 cm cm 2 cm
1.5	cm 2 cm
leight 8.0	2 cm
l l	
Depth 13.	471.
let weight 0.9	17 Kg
Gross weight 1.1	78 kg
P Code IP 4	14
Safety class	
Assembly Sur	face
Assembly details Wal	
Vattage 10 V	W
umen 420	) lm
Colour temperature 300	00 Kelvin
Color anti	hracite
<b>CRI</b> >80	)
XXBXX data 70/	50
Service life 400	000 h
Maximum ambient temperature 40	°C

								4				4			4		4		4	4	4	4	-4	4	4	4	4	4									
	- 4		a,		a,	4	a,	4	J	J	J.	J	J	J	J	J	a,	a,	a,	ä																	
ı	1	1	ı	ı	J	1	4	1	4	J	1	4	J	J	4	J	1	J		a.			J.		1		1	J	ı	J.	J.	ı	ı	ı	J.	ı	1
						a.			a.		а		a.	a.	а	a.	a.	J.	J.	J.	J.	a.	a.	a.	ı	ı	ă,	a.	ă.								



BIG WHITE Page	692
----------------	-----

Notes			