



Main

Range	Pragma
Product or component type	Door
Accessory / separate part category	Enclosure accessories
Market segment	Residential Small commercial

Complementary

Enclosure mounting	Flush Surface
Key number	Number to be stated
Type of front cover	Transparent
Door opening side	Right or left
Number of horizontal rows	6
9 mm pitches	48
Number of 18 mm modules per row	24
Total number of 18 mm modules	144
Installation description	Surface mounting Flush mounting
Enclosure material	Glass Metal
Width	550 mm
Height	1050 mm
Depth	20 mm
Colour	Colourless

Environment

Fire resistance	750 °C
-----------------	--------

IP degree of protection	IP40
IK degree of protection	IK09
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.6 kg
Package 1 Height	7 cm
Package 1 width	65 cm
Package 1 Length	114 cm
Unit Type of Package 2	P12
Number of Units in Package 2	15
Package 2 Weight	156.15 kg
Package 2 Height	120 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------