

DATA SHEET: HOLDER WITH CONDUCTIVE PROBES



SCHRACK-INFO

- Max. temperature up to 70 °C
- Max. range of pressure 1000 kPa
- Use in all areas, except in special areas of the food industry, where nylon 66 is not approved as an insulator
- Coated with nylon 66

TECHNICAL DATA

Holder / Conductive Probe	
Material	Nylon
Thread	1.5 inch BSP
Protection class	IP 65
Max. temperature	+ 70°C
Conductor / Electrode Rods	
Material	Stainless steel 316
Coating	Black powder epoxy
Length	1m
Number of Conductors	URL90010 1 x 1 metre rod URL90020 2 x 1 metre rod URL90030 3 x 1 metre rod
Optionale Stabverlängerungen	
Material	Stainless steel 316
Coating	Black powder epoxy
Length	1m
Connection	Thread (male and female)
Note	
Coating of rods improves resistance to false switching caused by frothing of condensation.	

DIMENSIONS



DESCRIPTION	EAN CODE	ORDER NO.
Holder with 1 conductive probe	9004840203264	URL90010
Holder with 2 conductive probes	9004840203271	URL90020
Holder with 3 conductive probes	9004840203288	URL90030
Extension rods 1000mm	9004840533415	URL90040