Locks and Lock Inserts























Schrack-Info

- Versatile selection of locks and lock inserts for retrofitting
- PU: Each 1 piece

| D FO COUNTY OF 1 | | 000000000 |
|--|---|-----------|
| DESCRIPTION | AVAILABLE | ORDER NO. |
| Mini-Swing Handle with Lock Insert | | |
| Mini-Swing handle with 5 mm double-bit insert, standard | | WSTS3532 |
| Mini-Swing handle with 8 mm square insert | 223 0-95 | WSTS3525 |
| Mini-Swing handle with 9 mm triangle insert | 200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | WSTS3529 |
| Mini-Swing handle with half cylinder insert 5333 (identical key) | 223 0- 22 2000 1-2 | WSTS5333 |
| Swing Handle without Lock Insert | | |
| Swing handle for half cylinder locks, IP65 | 350 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | IU001225 |
| Swing handle 1125-U 186 for half cylinder locks | 7777 C-75 | IU001903 |
| Quarter turn for half cylinder locks instead of WST sash locks | 333 0- 3 | IU001925 |
| Lock Inserts for Swing Handle | | |
| Half cylinder lock keyed EK 333 including 1 key | 223 0- 2 | DV900333 |
| Half cylinder lock keyed H36000 including 3 keys, L=40 mm | 2000 Dail 195 | IL900381 |
| Half cylinder lock with double-bit insert 5 mm, L=40 mm | 22.2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | IU001906 |
| Plastic Sash Lock with Lock Insert | | |
| Sash lock with 5 mm double-bit insert, standard | 7573 00 00 00 00 00 00 00 00 00 00 00 00 00 | WSTL3532 |

Locks and Lock Inserts

| DESCRIPTION | AVAILABLE | ORDER NO. |
|---|--|-----------|
| Lock Inserts for Plastic Sash Lock | | |
| Cylinder lock keyed 5333 including 1 key | 157 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | DV905333 |
| Double-bit insert 5 mm | 300 00 00 | WSTL3535 |
| Square insert 8 mm | 100 may 100 mg 1 | WSTL3525 |
| Triangle insert 9 mm | 300 0 0 0 | WSTL3529 |
| Keys | | |
| Key for 5 mm double-bit | 333 G G | DV903532 |
| Key for 8 mm square | 3000 Ger (5) | DV903525 |
| Key for 9 mm triangle | 350 0 0 0 0 | DV903529 |
| Key 333 for half cylinder lock DV900333 | 333 0= 0 | DV900334 |
| Key 5333 for AT/KT push-pull handle ATLSC501 and WST lock insert DV905333 | 2000 3 | DV905334 |

Door-Mounting Profiles



WSTCP0400

Schrack-Info

- Profiles to create additional mounting surfaces on the inside of the door
- In widths 400, 500, 600 and 800 mm available
- Mounting: into the door frame
- Material: 2 mm galvanised steel
- PU: 1 piece with mounting material
- For WST double door enclosures in width 1000 mm, the 500 mm wide door-mounting profiles WSTCP0500 respectively in width 1200 mm, the 600 mm wide door-mounting profiles WSTCP0600 can be used in the left and right door wing

| DESCRIPTION | AVAILABLE | ORDER NO. |
|---|---------------------|-----------|
| For 400 mm wide enclosures | 333 0-3 | WSTCP0400 |
| For 500 mm wide enclosures | 3000 000 | WSTCP0500 |
| For 600 mm wide enclosures | 353 0= 0 | WSTCP0600 |
| For 800 mm wide and 800/1000 mm high enclosures | 353 0- 9 | WSTCP0800 |
| For 800 mm wide and 1200 mm high enclosures | 353 0-3 | WSTCP0812 |