

DATA SHEET:
MEDIA ENCLOSURES SERIES AMPARO IP30 WITH SHEET STEEL DOOR



BK085733



BK085733



BK085703-F



BK071055




BK085094



SCHRACK-INFO

- 3- to 4-row media enclosure for solid wall or partition wall
- Frame and door in coated sheet steel, media distributor door with ventilation slots and door clip
- Frame design high (ca. 6mm)
- Available as a complete media enclosure with wall box (ABS, halogen free) or as a version with frame, door and insert, if the wall box is already present
- With a mounting rail on top of each enclosure, 12+2HP for insertion of patch modules
- Mounting plates for active and passive components included
- Glow wire test:
 - Resistant to abnormal heat and fire up to 850°C for partition walls
 - Resistant to abnormal heat and fire up to 650°C for solid walls
- Mounting bracket:
 - For partition walls (up to 30mm wall thickness)
 - For solid walls: Dovetail mounting brackets for front or back panel mounting
- Device holder (BK085094), double socket incl. EURO2-adapter with plug-in terminal up to 2.5mm² (BK071055) and wall box brackets horizontal (BK085098) as well as vertical (BK085095) can be obtained as accessory
- Protection class II
- Degree of protection IP30


DIMENSIONS



Article number	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	Rows	DIN-rail	MW	Mounting plates	Radiant power loss [W]*
BK085733	592	346	94	549	306	87	3	1	14	2	-45
BK085734	717	346	94	673	306	87	4	1	14	3	-54
BK085743	592	346	94	549	306	87	3	1	14	2	-45
BK085744	717	346	94	673	306	87	4	1	14	3	-54

*Max. radiated power of housing calculated as a wall-mounted single fixed with $\Delta T = 35K$.

FLUSH-MOUNTING DIMENSIONS



Article number		Solid wall cutout			Partition wall cutout		Rows	DIN-rail	MW
Flush-mounted enclosures	Partition wall	A [mm]	B [mm]	C [mm]	A [mm]	B [mm]			
BK085733	BK085743	562	320	90	533	310	3	1	14
BK085734	BK085744	685	320	90	677	310	4	1	14

■ MEDIA ENCLOSURES SERIES AMPARO IP30 WITH SHEET STEEL DOOR

DESCRIPTION	WxHxD mm	ORDER NO.
Solid wall		
Frame with door from sheet steel, insert and wall box		
3-rows, 1 DIN-rail 14 MW, 2 mounting plates	346x592x87	BK085733
4-rows, 1 DIN-rail 14 MW, 3 mounting plates	346x717x87	BK085734
Wall box for solid wall		
3-rows	306x549x87	BK0850032A
4-rows	306x673x87	BK0850042A
Frame with door from sheet steel and insert		
3-rows, 1 DIN-rail 14 MW, 2 mounting plates	346x592x36	BK085703-F
4-rows, 1 DIN-rail 14 MW, 3 mounting plates	346x717x36	BK085704-F
Partition wall		
Frame with door from sheet steel, insert and wall box		
3-rows, 1 DIN-rail 14 MW, 2 mounting plates	346x592x87	BK085743
4-rows, 1 DIN-rail 14 MW, 3 mounting plates	346x717x87	BK085744
Wall box for partition wall		
3-rows	306x549x87	BK0850532A
4-rows	306x673x87	BK0850542A
Frame with door from sheet steel and insert		
3-rows, 1 DIN-rail 14 MW, 2 mounting plates	346x592x36	BK085703-F
4-rows, 1 DIN-rail 14 MW, 3 mounting plates	346x717x36	BK085704-F
Accessories		
Socket for media enclosure, plug-in design		BK071055
Device holder		BK085094
Connection bracket set horizontal (PU= 2 pcs.)		BK085098
Connection bracket set vertical (PU= 2 pcs.)		BK085095
Half cylinder lock for BK085, plastic		BK085096
Half cylinder lock for BK085, metal		BK085097