# LED ROAD LIGHT ROUTE SMD





#### Technical details:

◆ Power :30W; 50W; 100W; 150W◆ Rated voltage: 100-265V/AC

◆ Frequency: 50/60Hz

◆ Power supply: Isolated driver

◆ Light source: Sanan◆ LED type: SMD

◆ Color temperature: 5000-5500K

◆ Beam angle: 85°X140°

◆ Ambient temperature: -35°C÷ +45°C

◆ CRI> 80

◆ Average lifetime: 20 000 hours

◆ PF> 0.9

◆ Body material: Aluminium

◆ Cover material: PC

◆ Protection against dust and moisture: IP65



#### Features:

- ◆ Completely replaces traditional street lamps
- ◆ Ultra- thin design
- ◆ Wide distribution of homogeneous, highly efficient light
- ◆ Economic- low power consumption
- ◆ Repeated switch on/off does not effect the fixture lifespan
- ◆ Instant light at maximum luminous flux
- ◆ Environmentally friendly no mercury and lead
- ◆ No ultraviolet and infrared rays
- ◆ Resistant to shock and vibration stable body
- ◆ Voltage supply fluctuations do not affect the normal operation of the fixture

## Application:

- ◆ Roads, High ways.
- ◆ Urban Street, Bridge, Pavement.
- ◆ Square, School, Residential, Park and other outdoor place.
- ◆ Underground Parking Garage, Parking Lot.

#### Product details:

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp (K)	Beam angle
98ROUTE30SMD	30	3000	5000-5500	85°x140°
98ROUTE50SMD	50	5000	5000-5500	85°x140°
98ROUTE100SMD	100	10000	5000-5500	85°x140°
98ROUTE150SMD	150	15000	5000-5500	85°x140°


www.elmarkholding.eu

# **TECHNICAL SPECIFICATION**


**ROUTE SMD** 



#### **Dimensions:**



Model	Length (mm)	Width (mm)	Height (mm)
98ROUTE30SMD	130	53	340
98ROUTE50SMD	155	55	390
98ROUTE100SMD	160	65	450
98ROUTE150SMD	170	65	570



### Packing:

Model	Packing/Box (pcs)
98ROUTE30SMD	1/1
98ROUTE50SMD	1/1
98ROUTE100SMD	1/1
98ROUTE150SMD	1/1

