



**243.32965**

## FLUSH MOUNTING APPLIANCE INLET

32A 3P+E 11h 440-460V 60Hz 75X75MM Screw terminals

Product Approvals

| TECHDATA                   |                                | STANDARDS AND LAWS                |                                                                                                                                                                                                       |
|----------------------------|--------------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of product            | FLUSH MOUNTING APPLIANCE INLET | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Commercial series          | OPTIMA Series                  | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | FLUSH MOUNTING APPLIANCE INLET |                                   |                                                                                                                                                                                                       |
| Mounting version           | FLUSH MOUNTING                 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Rated current              | 32A                            |                                   |                                                                                                                                                                                                       |
| Poles                      | 3P+E                           |                                   |                                                                                                                                                                                                       |
| Hour position              | 11h                            |                                   |                                                                                                                                                                                                       |
| Rated voltage (range)      | 400-up                         |                                   |                                                                                                                                                                                                       |
| Rated voltage              | 440-460V                       |                                   |                                                                                                                                                                                                       |
| Working frequency          | 60Hz                           |                                   |                                                                                                                                                                                                       |
| Colour                     | RED                            |                                   |                                                                                                                                                                                                       |
| Material                   | THERMOPLASTIC                  |                                   |                                                                                                                                                                                                       |
| Protection degree          | Splash proof                   |                                   |                                                                                                                                                                                                       |
| Protection degree IP       | IP44/IP54                      |                                   |                                                                                                                                                                                                       |
| Protection degree IK       | IK08                           |                                   |                                                                                                                                                                                                       |
| Types of available outlets | STRAIGHT                       |                                   |                                                                                                                                                                                                       |
| Terminals                  | Screw terminals                |                                   |                                                                                                                                                                                                       |
| Contact material           | CuZn (brass)                   |                                   |                                                                                                                                                                                                       |

|                            |               |
|----------------------------|---------------|
| Surface treatment contacts | Nickel-plated |
| Flange                     | 75X75MM       |