



247.16934

FLUSH MOUNTING APPLIANCE INLET

16A 2P+E 3h >50-250V DC 70X87MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|--------------------------------|-----------------------------------|---|
| Commercial series | EUREKA Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | FLUSH MOUNTING APPLIANCE INLET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET | | |
| Mounting version | FLUSH/SURFACE MOUNTING | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Rated current | 16A | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles | 2P+E | | |
| Hour position | 3h | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated voltage (range) | 50-200V | | |
| Rated voltage | >50-250V | | |
| Working frequency | DC | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK07 | | |
| Types of available outlets | 90° ANGLED | | |
| Terminals | Screw terminals | | |

| | |
|----------------------------|---------------|
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |
| Flange | 70X87MM |
| Cable entry | PG 16 |