

## Product Technical Sheet

12 Aug 2021 07:20



# 423.16632

## FLUSH-MOUNTING SOCKET

16A 2P+E 2h >50V >300-500Hz 75X75MM

Screw terminals

Product Approvals

| TECHDATA                   |                       | STANDARDS AND LAWS                |                                                                                                                                                                                                       |
|----------------------------|-----------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial series          | OPTIMA Series         | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Type of product            | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | FLUSH-MOUNTING SOCKET |                                   |                                                                                                                                                                                                       |
| Mounting version           | FLUSH MOUNTING        | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Rated current              | 16A                   | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles                      | 2P+E                  |                                   |                                                                                                                                                                                                       |
| Hour position              | 2h                    |                                   |                                                                                                                                                                                                       |
| Rated voltage (range)      | 50-200V               | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Rated voltage              | >50V                  | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Working frequency          | >300-500Hz            |                                   |                                                                                                                                                                                                       |
| Colour                     | GREEN                 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Material                   | THERMOPLASTIC         |                                   |                                                                                                                                                                                                       |
| Protection degree          | Splash proof          |                                   |                                                                                                                                                                                                       |
| Protection degree IP       | IP44/IP54             |                                   |                                                                                                                                                                                                       |
| Protection degree IK       | IK08                  |                                   |                                                                                                                                                                                                       |
| Types of available outlets | STRAIGHT              |                                   |                                                                                                                                                                                                       |
| Terminals                  | Screw terminals       |                                   |                                                                                                                                                                                                       |
| Contact material           | CuZn (brass)          |                                   |                                                                                                                                                                                                       |

|        |         |
|--------|---------|
| Flange | 75X75MM |
|--------|---------|