Product Technical Sheet

12 Aug 2021 07:31





527.3254

SURFACE MOUNTING SOCKET

32A 3P+E 9h 200-250V 50Hz 60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | S AND LAWS |
|----------------------------|----------------------------|--|--|
| Type of product | SURFACE MOUNTING SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | OPTIMA Series | EN 60309-2 (1999) [European Standard] Plugs, socket-outle and couplers for industrial purposes. Pa 2: Dimensional interchangeability requirements for pin and contact-tube | [European Standard] Plugs, socket-outlets |
| Synthetical description | SURFACE MOUNTING SOCKET | | 2: Dimensional interchangeability |
| Mounting version | SURFACE MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 | [European Directives] Low Voltage Directive |
| Rated current | 32A | /UE | |
| Poles | 3P+E | | |
| Hour position | 9h | | |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | 200-250V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | BLUE | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67/IP69 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | STRAIGHT | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|------------------|---------------------|--|
| Cable entry | DRILLING POINT MARK | |