



## 513.3258T

### SURFACE MOUNTING SOCKET

32A 2P+E 9h 380-415V 50Hz 60Hz Screw  
terminals

Product Approvals

| TECHDATA                   |                            | STANDARDS AND LAWS                      |                                                                                                                                                                                                       |
|----------------------------|----------------------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of product            | SURFACE MOUNTING<br>SOCKET | EN 60309-1 (1999)                       | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Commercial series          | OPTIMA-TOP Series          | EN 60309-2 (1999)                       | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | SURFACE MOUNTING<br>SOCKET |                                         |                                                                                                                                                                                                       |
| Mounting version           | SURFACE MOUNTING           | EN 60309-1/A1 (2007)                    | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Rated current              | 32A                        | EN 60309-2/A1 (2007)                    | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles                      | 2P+E                       |                                         |                                                                                                                                                                                                       |
| Hour position              | 9h                         |                                         |                                                                                                                                                                                                       |
| Rated voltage (range)      | 250-400V                   | DIRECTIVE LOW<br>VOLTAGE 2014/35<br>/UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Rated voltage              | 380-415V                   |                                         |                                                                                                                                                                                                       |
| Working frequency          | 60Hz                       |                                         |                                                                                                                                                                                                       |
| Working frequency          | 50Hz                       |                                         |                                                                                                                                                                                                       |
| Colour                     | RED                        |                                         |                                                                                                                                                                                                       |
| Material                   | THERMOPLASTIC              |                                         |                                                                                                                                                                                                       |
| Protection degree          | Splash proof               |                                         |                                                                                                                                                                                                       |
| Protection degree IP       | IP44                       |                                         |                                                                                                                                                                                                       |
| Protection degree IK       | IK08                       |                                         |                                                                                                                                                                                                       |
| Types of available outlets | ANGLED                     |                                         |                                                                                                                                                                                                       |
| Terminals                  | Screw terminals            |                                         |                                                                                                                                                                                                       |

|                  |              |
|------------------|--------------|
| Contact material | CuZn (brass) |
| Cable entry      | M32X1,5      |