

Product Technical Sheet

12 Aug 2021 07:49



435.16164/R

FLUSH-MOUNTING SOCKET

16A 2P 3h 20-25V 40-50V 400Hz 55X55MM
Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|-----------------------|--------------------|---|
| Commercial series | IEC309 Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | FLUSH-MOUNTING SOCKET | | |
| Mounting version | FLUSH MOUNTING | | |
| Rated current | 16A | | |
| Poles | 2P | | |
| Hour position | 3h | | |
| Rated voltage (range) | 0-50V | | |
| Rated voltage | 40-50V | | |
| Rated voltage | 20-25V | | |
| Working frequency | 400Hz | | |
| Colour | GREEN | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Types of available outlets | STRAIGHT | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |

Flange

55X55MM