



# 248.12597.MIL

## FLUSH MOUNTING APPLIANCE INLET

125A 3P+N+E 6h 346-415V 50Hz 60Hz  
114X114MM Mantle terminals

Product Approvals

| TECHDATA                   |                                | STANDARDS AND LAWS                |   |
|----------------------------|--------------------------------|-----------------------------------|---|
| Type of product            | FLUSH MOUNTING APPLIANCE INLET | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Commercial series          | OPTIMA-MIL Series              | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | FLUSH MOUNTING APPLIANCE INLET |                                   |   |
| Mounting version           | FLUSH MOUNTING                 | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Rated current              | 125A                           | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles                      | 3P+N+E                         |                                   |   |
| Hour position              | 6h                             |                                   |   |
| Rated voltage (range)      | 250-400V                       | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Rated voltage              | 346-415V                       | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Working frequency          | 60Hz                           |                                   |   |
| Working frequency          | 50Hz                           |                                   |   |
| Colour                     | RED                            | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Material                   | THERMOPLASTIC                  |                                   |   |
| Protection degree          | Watertight                     |                                   |   |
| Protection degree IP       | IP66/IP67/IP69                 |                                   |   |
| Protection degree IK       | IK08                           |                                   |   |
| Types of available outlets | STRAIGHT                       |                                   |   |
| Terminals                  | Mantle terminals               |                                   |   |

|                            |               |
|----------------------------|---------------|
| Contact material           | CuZn (brass)  |
| Surface treatment contacts | Nickel-plated |
| Flange                     | 114X114MM     |