



# SCM3100R5W RECEPTACLE

100A 2P 3W 5h 277V 145X145MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Type of product	RECEPTACLE		
Synthetical description	RECEPTACLE		
Mounting version	FLUSH MOUNTING	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Rated current	100A	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Poles	2P 3W		
Hour position	5h	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Rated voltage (range)	250-400V		
Rated voltage	277V		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	145X145MM		