



SCM330B4W

FLUSH MOUNTING APPLIANCE INLET

30A 2P 3W 4h 125V 120X120MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Type of product	FLUSH MOUNTING APPLIANCE INLET		
Synthetical description	FLUSH MOUNTING APPLIANCE INLET	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Mounting version	FLUSH MOUNTING	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Rated current	30A	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Poles	2P 3W		
Hour position	4h		
Rated voltage (range)	50-200V		
Rated voltage	125V		
Colour	YELLOW		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	90° ANGLED		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Surface treatment contacts	Nickel-plated		

Flange

120X120MM