



SCM330B5S

FLUSH MOUNTING APPLIANCE INLET

30A 2P 3W 5h 277V 120X120MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Type of product	FLUSH MOUNTING APPLIANCE INLET		
Synthetical description	FLUSH MOUNTING APPLIANCE INLET	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Mounting version	FLUSH MOUNTING		
Rated current	30A		
Poles	2P 3W		
Hour position	5h		
Rated voltage (range)	250-400V		
Rated voltage	277V		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK10		
Types of available outlets	90° ANGLED		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Surface treatment contacts	Nickel-plated		

Flange

120X120MM