

## Product Technical Sheet

12 Aug 2021 07:57



# SCM330P8S

## PLUG

30A 2P 3W 8h 550VDC Screw terminals



Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	PLUG	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Commercial series	EUREKA-HD[UL] Series	UL 486E	[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors
Synthetical description	PLUG	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Mounting version	PORTABLE	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Rated current	30A		
Poles	2P 3W		
Hour position	8h		
Rated voltage (range)	400-up		
Rated voltage	550VDC		
Colour	BLACK		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Surface treatment contacts	Nickel-plated		

