



SCM330R7W RECEPTACLE

30A 2P 3W 7h 480V 75X75MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	RECEPTACLE	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Commercial series	EUREKA-HD[UL] Series		
Synthetical description	RECEPTACLE		
Mounting version	FLUSH MOUNTING	IEC 60309-1 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Rated current	30A	IEC 60309-2 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Poles	2P 3W		
Hour position	7h	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Rated voltage (range)	400-up		
Rated voltage	480V	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Colour	RED		
Material	THERMOPLASTIC	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	75X75MM		