## **Product Technical Sheet**

12 Aug 2021 07:58





## SCM332B6W FLUSH MOUNT

## FLUSH MOUNTING APPLIANCE INLET

32A 2P 3W 6h 200-250V 50/60Hz 120X120MM Screw terminals

**Product Approvals** 

| TECHDATA                   |                                   | STANDARDS                        | AND LAWS  |
|----------------------------|-----------------------------------|----------------------------------|---|
| Type of product            | FLUSH MOUNTING<br>APPLIANCE INLET | IEC 60309-1 (2012)               | [International Standard] Plugs, socket-<br>outlets and couplers for industrial<br>purposes Part 1: General requirements |
| Commercial series          | EUREKA-HD[UL] Series              | OL                               | [International Standard] Plugs, socket-<br>outlets and couplers for industrial  |
| Synthetical description    | FLUSH MOUNTING<br>APPLIANCE INLET |                                  | purposes Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories                      |
| Mounting version           | FLUSH MOUNTING                    | DIRECTIVE LOW<br>VOLTAGE 2014/35 | [European Directives] Low Voltage Directive   |
| Rated current              | 32A                               | /UE                              |   |
| Poles                      | 2P 3W                             |                                  |   |
| Hour position              | 6h                                |                                  |   |
| Rated voltage (range)      | 200-250V                          |                                  |   |
| Rated voltage              | 200-250V                          |                                  |   |
| Working frequency          | 50/60Hz                           |                                  |   |
| Colour                     | BLUE                              |                                  |   |
| Material                   | THERMOPLASTIC                     |                                  |   |
| Protection degree          | Watertight                        |                                  |   |
| Protection degree IP       | IP67                              |                                  |   |
| Protection degree IK       | IK10                              |                                  |   |
| Types of available outlets | 90° ANGLED                        |                                  |   |
| Terminals                  | Screw terminals                   |                                  |   |
| Contact material           | CuZn (brass)                      |                                  |   |

| Surface treatment contacts | Nickel-plated |  |
|----------------------------|---------------|--|
| Flange                     | 120X120MM     |  |