Product Technical Sheet

12 Aug 2021 07:59





SCM360P5W PLUG

60A 2P 3W 5h 277V Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and
Type of product	PLUG		Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe
Synthetical description	PLUG		flexing service
Mounting version	PORTABLE	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Rated current	60A	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Poles	2P 3W		
Hour position	5h	CSA C22.2 No. 65- 93	[Canadian Standard] Wire connectors wiring products
Rated voltage (range)	250-400V		
Rated voltage	277V		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Surface treatment contacts	Nickel-plated		