Product Technical Sheet

12 Aug 2021 07:59





SCM360P8W PLUG

60A 2P 3W 8h 550VDC Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | S AND LAWS |
|----------------------------|----------------------|---|--|
| Type of product | PLUG | UL 1682 [American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service | |
| Commercial series | EUREKA-HD[UL] Series | | heavy duty, portable, power, single and |
| Synthetical description | PLUG | | flexing service |
| Mounting version | PORTABLE | UL 486E | [American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors |
| Rated current | 60A | CSA C22.2 No. 182.1 (1988) | [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products |
| Poles | 2P 3W | | |
| Hour position | 8h | CSA C22.2 No. 65- 93 | |
| Rated voltage (range) | 400-up | | |
| Rated voltage | 550VDC | | |
| Colour | BLACK | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP67 | | |
| Protection degree IK | IK10 | | |
| Types of available outlets | STRAIGHT | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Surface treatment contacts | Nickel-plated | | |
| | | | |