



SCM416R6W RECEPTACLE

16A 3P 4W 6h 380-415V 50/60Hz 75X75MM
Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	EUREKA-HD[UL] Series	IEC 60309-1 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Type of product	RECEPTACLE	IEC 60309-2 (1999)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Synthetical description	RECEPTACLE		
Mounting version	FLUSH MOUNTING		
Rated current	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	3P 4W		
Hour position	6h		
Rated voltage (range)	250-400V		
Rated voltage	380-415V		
Working frequency	50/60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Flange

75X75MM