



# SCM420R6W RECEPTACLE

20A 3P 4W 6h 3Ø380-415V 75X75MM Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	RECEPTACLE	UL 1682	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Commercial series	EUREKA-HD[UL] Series		
Synthetical description	RECEPTACLE	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors
Mounting version	FLUSH MOUNTING		
Rated current	20A	CSA C22.2 No. 182.1 (1988)	[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Poles	3P 4W		
Hour position	6h	CSA C22.2 No. 65-93	[Canadian Standard] Wire connectors wiring products
Rated voltage (range)	250-400V	IEC 60309-1 (2012)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements
Rated voltage	3Ø380-415V	IEC 60309-2 (2012)	[International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	75X75MM		