



SCM460B7W

FLUSH MOUNTING APPLIANCE INLET

60A 3P 4W 7h 3Ø480V 120X120MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|--------------------------------|----------------------------|---|
| Type of product | FLUSH MOUNTING APPLIANCE INLET | UL 1682 | [American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service |
| Commercial series | EUREKA-HD[UL] Series | | |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET | UL 486E | [American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors |
| Mounting version | FLUSH MOUNTING | CSA C22.2 No. 182.1 (1988) | [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products |
| Rated current | 60A | CSA C22.2 No. 65-93 | [Canadian Standard] Wire connectors wiring products |
| Poles | 3P 4W | | |
| Hour position | 7h | | |
| Rated voltage (range) | 400-up | | |
| Rated voltage | 3Ø480V | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP67 | | |
| Protection degree IK | IK10 | | |
| Types of available outlets | 90° ANGLED | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Surface treatment contacts | Nickel-plated | | |

Flange

120X120MM