Product Technical Sheet

12 Aug 2021 08:03





SCM460B9W

FLUSH MOUNTING APPLIANCE INLET

60A 3P 4W 9h 3Ø250V 120X120MM Screw terminals

Product Approvals

TECHDATA		STANDARDS	S AND LAWS
Type of product	FLUSH MOUNTING APPLIANCE INLET	UL 1682 [American Standard] Plugs, and Cable Connectors of the Sleeve Type and MIL-C-575 heavy duty, portable, power, multiconductor, electrical cal	[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt
Commercial series	EUREKA-HD[UL] Series		heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
Synthetical description	FLUSH MOUNTING APPLIANCE INLET	UL 486E	[American Standard] Equipment wiring terminals for use with aluinium and/or
Mounting version	FLUSH MOUNTING	CSA C22.2 No. 182.1 (1988)	copper conductors [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
Rated current	60A		
Poles	3P 4W	CSA C22.2 No. 65- 93	SA C22.2 No. 65- [Canadian Standard] Wire connectors
Hour position	9h	93	wining products
Rated voltage (range)	250-400V		
Rated voltage	3Ø250V		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Protection degree IK	IK10		
Types of available outlets	90° ANGLED		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Surface treatment contacts	Nickel-plated		