



SCM520B6S

FLUSH MOUNTING APPLIANCE INLET

20A 4P 5W 6h 200/346V 240/415V 120X120MM
Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|--------------------------------|-----------------------------------|---|
| Commercial series | EUREKA-HD[UL] Series | UL 1682 | [American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service |
| Type of product | FLUSH MOUNTING APPLIANCE INLET | | |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET | UL 486E | [American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors |
| Mounting version | FLUSH MOUNTING | CSA C22.2 No. 182.1 (1988) | [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products |
| Rated current | 20A | CSA C22.2 No. 65-93 | [Canadian Standard] Wire connectors wiring products |
| Poles | 4P 5W | IEC 60309-1 (2012) | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 1: General requirements |
| Hour position | 6h | IEC 60309-2 (2012) | [International Standard] Plugs, socket-outlets and couplers for industrial purposes. - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | 200/346V 240/415V | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK10 | | |
| Types of available outlets | 90° ANGLED | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Surface treatment contacts | Nickel-plated | | |

Flange

120X120MM