



# SCM560B9W

## FLUSH MOUNTING APPLIANCE INLET

60A 4P 5W 9h 3ØY120/208V 120X120MM  
Screw terminals

Product Approvals

| TECHDATA                   |                                | STANDARDS AND LAWS         |                                                                                                                                                                                                                       |
|----------------------------|--------------------------------|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial series          | EUREKA-HD[UL] Series           | UL 1682                    | [American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service |
| Type of product            | FLUSH MOUNTING APPLIANCE INLET |                            |                                                                                                                                                                                                                       |
| Synthetical description    | FLUSH MOUNTING APPLIANCE INLET | UL 486E                    | [American Standard] Equipment wiring terminals for use with aluinium and/or copper conductors                                                                                                                         |
| Mounting version           | FLUSH MOUNTING                 | CSA C22.2 No. 182.1 (1988) | [Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products                                                                                               |
| Rated current              | 60A                            | CSA C22.2 No. 65-93        | [Canadian Standard] Wire connectors wiring products                                                                                                                                                                   |
| Poles                      | 4P 5W                          |                            |                                                                                                                                                                                                                       |
| Hour position              | 9h                             |                            |                                                                                                                                                                                                                       |
| Rated voltage (range)      | 50-200V                        |                            |                                                                                                                                                                                                                       |
| Rated voltage              | 3ØY120/208V                    |                            |                                                                                                                                                                                                                       |
| Colour                     | BLUE                           |                            |                                                                                                                                                                                                                       |
| Material                   | THERMOPLASTIC                  |                            |                                                                                                                                                                                                                       |
| Protection degree          | Watertight                     |                            |                                                                                                                                                                                                                       |
| Protection degree IP       | IP67                           |                            |                                                                                                                                                                                                                       |
| Protection degree IK       | IK10                           |                            |                                                                                                                                                                                                                       |
| Types of available outlets | 90° ANGLED                     |                            |                                                                                                                                                                                                                       |
| Terminals                  | Screw terminals                |                            |                                                                                                                                                                                                                       |
| Contact material           | CuZn (brass)                   |                            |                                                                                                                                                                                                                       |
| Surface treatment contacts | Nickel-plated                  |                            |                                                                                                                                                                                                                       |

|        |           |
|--------|-----------|
| Flange | 120X120MM |
|--------|-----------|