Product Technical Sheet

12 Aug 2021 08:07





240.3297-7

SURFACE MOUNT. APPLIANCE INLET

32A 6P+E 6h 380-415V 50Hz 60Hz Screw terminals

Product Approvals

TECHDATA		STANDARDS	S AND LAWS
Type of product	SURFACE MOUNT. APPLIANCE INLET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	OPTIMA-SEVEN Series	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Synthetical description	SURFACE MOUNT. APPLIANCE INLET	EN 60309-1/A2 (2012)	General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Mounting version	SURFACE MOUNTING	1: General requirements DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive /UE	
Rated current	32A		
Poles	6P+E		
Hour position	6h		
Rated voltage (range)	250-400V		
Rated voltage	380-415V		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK08		
Types of available outlets	ANGLED		
Terminals	Screw terminals		

Contact material	CuZn (brass)	
Surface treatment contacts	Nickel-plated	
Cable entry	M25X1,5	