



400.16838

INTERLOCKED SOCKET

16A 2P+E 8h >250V DC 136X125MM Screw terminals With mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	OMNIA Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	FLUSH MOUNTING		
Rated current	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	2P+E		
Hour position	8h		
Rated voltage (range)	250-400V		
Rated voltage	>250V		
Working frequency	DC		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK08		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	136X125MM		

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER