

# 405.16864

## INTERLOCKED SOCKET

16A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz 136X125MM Screw terminals With  
mechanical interlock



Product Approvals

| TECHDATA                |                       | STANDARDS AND LAWS                |   |
|-------------------------|-----------------------|-----------------------------------|---|
| Commercial series       | OMNIA Series          | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Type of product         | INTERLOCKED SOCKET    | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET    |                                   |   |
| Mounting version        | FLUSH MOUNTING        |                                   |   |
| Rated current           | 16A                   | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poles                   | 3P+E                  | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position           | 3h                    |                                   |   |
| Rated voltage (range)   | 250-400V              | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Rated voltage           | 380V 50Hz / 440V 60Hz |                                   |   |
| Working frequency       | 60Hz                  | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Working frequency       | 50Hz                  | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colour                  | RED                   |                                   |   |
| Material                | THERMOPLASTIC         |                                   |   |
| Protection degree       | Watertight            | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Protection degree IP    | IP66/IP67             |                                   |   |
| Protection degree IK    | IK08                  | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Terminals               | Screw terminals       |                                   |   |
| Contact material        | CuZn (brass)          |                                   |   |

|         |                           |
|---------|---------------------------|
| Flange  | 136X125MM                 |
| Options | With mechanical interlock |
| Notes   | WITHOUT FUSE HOLDER       |