

**406.1672**

## INTERLOCKED SOCKET

16A 3P+E 4h 100-130V 50Hz 60Hz

136X125MM Screw terminals With mechanical interlock



Product Approvals

| TECHDATA                |                    | STANDARDS AND LAWS                |                                                                                                                                                                                                       |
|-------------------------|--------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial series       | OMNIA Series       | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Type of product         | INTERLOCKED SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET |                                   |                                                                                                                                                                                                       |
| Mounting version        | FLUSH MOUNTING     |                                   |                                                                                                                                                                                                       |
| Rated current           | 16A                | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Poles                   | 3P+E               | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position           | 4h                 |                                   |                                                                                                                                                                                                       |
| Rated voltage (range)   | 50-200V            | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock                                                     |
| Rated voltage           | 100-130V           |                                   |                                                                                                                                                                                                       |
| Working frequency       | 60Hz               | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Working frequency       | 50Hz               | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colour                  | YELLOW             |                                   |                                                                                                                                                                                                       |
| Material                | THERMOPLASTIC      |                                   |                                                                                                                                                                                                       |
| Protection degree       | Watertight         | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Protection degree IP    | IP66/IP67          |                                   |                                                                                                                                                                                                       |
| Protection degree IK    | IK08               |                                   |                                                                                                                                                                                                       |
| Terminals               | Screw terminals    |                                   |                                                                                                                                                                                                       |
| Contact material        | CuZn (brass)       |                                   |                                                                                                                                                                                                       |

|         |                           |
|---------|---------------------------|
| Flange  | 136X125MM                 |
| Options | With mechanical interlock |
| Notes   | WITH FUSE HOLDER          |