

# 506.16834

## INTERLOCKED SOCKET

16A 2P+E 3h >50-250V DC 136X125MM\_PAR  
Screw terminals With mechanical interlock



Product Approvals

| TECHDATA                |                    | STANDARDS AND LAWS                |   |
|-------------------------|--------------------|-----------------------------------|---|
| Commercial series       | OMNIA Series       | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Type of product         | INTERLOCKED SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET |                                   |   |
| Mounting version        | SURFACE MOUNTING   |                                   |   |
| Rated current           | 16A                | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Poles                   | 2P+E               |                                   |   |
| Hour position           | 3h                 |                                   |   |
| Rated voltage (range)   | 50-200V            |                                   |   |
| Rated voltage           | >50-250V           |                                   |   |
| Working frequency       | DC                 |                                   |   |
| Colour                  | GREY               |                                   |   |
| Material                | THERMOPLASTIC      |                                   |   |
| Protection degree       | Watertight         |                                   |   |
| Protection degree IP    | IP66/IP67          |                                   |   |
| Protection degree IK    | IK08               |                                   |   |
| Terminals               | Screw terminals    |                                   |   |
| Contact material        | CuZn (brass)       |                                   |   |
| Flange                  | 136X125MM_PAR      |                                   |   |

|         |                           |
|---------|---------------------------|
| Options | With mechanical interlock |
| Notes   | WITH FUSE HOLDER          |