

## Product Technical Sheet

12 Aug 2021 08:25



# 561.32838

## INTERLOCKED SOCKET

32A 2P+E 8h >250V DC 106X240MM Screw terminals With mechanical interlock

Product Approvals

| TECHDATA                |                    | STANDARDS AND LAWS                |                                                                                                                                                                                                       |
|-------------------------|--------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial series       | ADVANCE 2 Series   | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements                                                                                          |
| Type of product         | INTERLOCKED SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET |                                   |                                                                                                                                                                                                       |
| Mounting version        | SURFACE MOUNTING   |                                   |                                                                                                                                                                                                       |
| Rated current           | 32A                | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                           |
| Poles                   | 2P+E               |                                   |                                                                                                                                                                                                       |
| Hour position           | 8h                 |                                   |                                                                                                                                                                                                       |
| Rated voltage (range)   | 250-400V           |                                   |                                                                                                                                                                                                       |
| Rated voltage           | >250V              |                                   |                                                                                                                                                                                                       |
| Working frequency       | DC                 |                                   |                                                                                                                                                                                                       |
| Colour                  | GREY               |                                   |                                                                                                                                                                                                       |
| Material                | THERMOPLASTIC      |                                   |                                                                                                                                                                                                       |
| Protection degree       | Watertight         |                                   |                                                                                                                                                                                                       |
| Protection degree IP    | IP66/IP67          |                                   |                                                                                                                                                                                                       |
| Protection degree IK    | IK07               |                                   |                                                                                                                                                                                                       |
| Terminals               | Screw terminals    |                                   |                                                                                                                                                                                                       |
| Contact material        | CuZn (brass)       |                                   |                                                                                                                                                                                                       |
| Flange                  | 106X240MM          |                                   |                                                                                                                                                                                                       |
|                         |                    |                                   |                                                                                                                                                                                                       |

|             |                           |
|-------------|---------------------------|
| Cable entry | M25X1,5                   |
| Options     | With mechanical interlock |
| Notes       | WITHOUT FUSE HOLDER       |
| Padlock     | ø5mm                      |