

Product Technical Sheet

12 Aug 2021 08:30



565.2416

INTERLOCKED SOCKET

16A 2P 24V 106X240MM Screw terminals With electrical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE 2 Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	2P		
Rated voltage (range)	0-50V		
Rated voltage	24V		
Colour	VIOLET		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	106X240MM		
Cable entry	M25X1,5		
Options	With electrical interlock		

Notes	CON TRASFORMATORE
Padlock	ø5mm