



## 403.63864-M

### INTERLOCKED SOCKET

63A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz 170X380MM Screw terminals With  
mechanical interlock

Product Approvals

#### TECHDATA

|                         |                                |
|-------------------------|--------------------------------|
| Type of product         | INTERLOCKED SOCKET             |
| Commercial series       | ADVANCE GRP Series             |
| Synthetical description | INTERLOCKED SOCKET             |
| Rated current           | 63A                            |
| Poles                   | 3P+E                           |
| Hour position           | 3h                             |
| Rated voltage (range)   | 250-400V                       |
| Rated voltage           | 380V 50Hz / 440V 60Hz          |
| Working frequency       | 50Hz                           |
| Working frequency       | 60Hz                           |
| Colour                  | RED                            |
| Material                | GRP Glass Reinforced Polyester |
| Protection degree       | Watertight                     |
| Protection degree IP    | IP66/IP67/IP69                 |
| Protection degree IK    | IK10                           |
| Terminals               | Screw terminals                |
| Contact material        | CuZn (brass)                   |
| Flange                  | 170X380MM                      |

|                         |                           |
|-------------------------|---------------------------|
| Working temperature     | -40°C/+60°C               |
| GLOW WIRE               | GW 960°C                  |
| Self-extinguishing UL94 | V0                        |
| Options                 | With mechanical interlock |
| Notes                   | WITHOUT FUSE HOLDER       |
| Padlock                 | ø6,3mm                    |