

## Product Technical Sheet

12 Aug 2021 08:45



# 579.5112

## MODULAR BASE

MODULAR BASE IP66/IP67/IP69 16A-32A

Product Approvals

| TECHDATA                |                                | STANDARDS AND LAWS                |                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection degree       | Watertight                     | EN 60670-1 (2005)                 | [European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations. General requirements                                                                                                             |
| Commercial series       | ADVANCE-GRP System             | EN 60670-24 (2013)                | [European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations - Part 24: Particular requirements for enclosures for housing protective devices and other power dissipating electrical equipment |
| Type of product         | MODULAR BASE                   |                                   |                                                                                                                                                                                                                                                                |
| Synthetical description | MODULAR BASE                   | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive                                                                                                                                                                                                                    |
| Material                | GRP Glass Reinforced Polyester |                                   |                                                                                                                                                                                                                                                                |
| Protection degree IP    | IP66/IP67/IP69                 |                                   |                                                                                                                                                                                                                                                                |
| Notes                   | 16A-32A                        |                                   |                                                                                                                                                                                                                                                                |
| Dimensions              | 130x460mm                      |                                   |                                                                                                                                                                                                                                                                |
| Flange                  | 130X460MM                      |                                   |                                                                                                                                                                                                                                                                |
| Dissipable power        | 9W                             |                                   |                                                                                                                                                                                                                                                                |
| Protection degree IK    | IK10                           |                                   |                                                                                                                                                                                                                                                                |
| GLOW WIRE               | GW 960°C                       |                                   |                                                                                                                                                                                                                                                                |
| Self-extinguishing UL94 | V0                             |                                   |                                                                                                                                                                                                                                                                |
| Working temperature     | -40°C/+60°C                    |                                   |                                                                                                                                                                                                                                                                |