



590.YM40B2

FRONT OPERATOR PADLOCKABLE

IP65 ø22mm ø40mm Y1 GENERAL BLACK 16A-40A

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	COMMAND Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type of product	FRONT OPERATOR PADLOCKABLE	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	FRONT OPERATOR PADLOCKABLE	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	THERMOPLASTIC	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	BLACK	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Switch size	Y1		
Rated voltage	690V		
Diameter	ø22mm		
Dimensions	ø40mm		
Notes	16A-40A		