



590.ER3205

SWITCH DISCONNECTOR

32A 3P+N IP65 136x125mm Y1 IK09
EMERGENCY YELLOW/RED GW 650°C

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Type of product | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-TP Series | | |
| Synthetical description | SWITCH DISCONNECTOR | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Material | ENGINEERING PLASTIC | | |
| Protection degree IP | IP65 | | |
| Type | EMERGENCY | | |
| Colour | YELLOW/RED | | |
| Rated current | 32A | | |
| Poles | 3P+N | | |
| Switch size | Y1 | | |
| Rated voltage | 690V | | |
| Dimensions | 136x125mm | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK09 | | |
| Flange | 136X125MM | | |