



590.EL2508

SWITCH DISCONNECTOR

25A 8P IP66/IP69 160x220x115mm Y3 IK09
GENERAL YELLOW/RED LOCKABLE ON-OFF
GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ISOLATORS-TP Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type of product	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP66/IP69	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	YELLOW/RED	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	25A		
Poles	8P		
Switch size	Y3		
Rated voltage	690V		
Dimensions	160x220x115mm		
Notes	LOCKABLE ON-OFF		
GLOW WIRE	GW 650°C		
Protection degree IK	IK09		