



## 590.EM4014

### SWITCH DISCONNECTOR

40A 4P IP66/IP69 110x150x87mm Y1 IK09  
EMERGENCY YELLOW/RED GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-TP Series		
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Protection degree IP	IP66/IP69		
Type	EMERGENCY	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	YELLOW/RED		
Rated current	40A	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Poles	4P	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Switch size	Y1		
Rated voltage	690V	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Dimensions	110x150x87mm		
GLOW WIRE	GW 650°C		
Protection degree IK	IK09		
Flange	106X150MM		