



# 590.MEM12505

## SWITCH DISCONNECTOR

125A 3P+N IP65 200x300x120mm Y5 IK10  
EMERGENCY YELLOW/RED

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ISOLATORS-MS Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type of product	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	VARNISHED METAL	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	EMERGENCY	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	YELLOW/RED	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	125A	DIRECTIVE RoHS 2011/65/EU	[European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment
Poles	3P+N		
Switch size	Y5		
Rated voltage	690V		
Dimensions	200x300x120mm		
Protection degree IK	IK10		