



590.KEM160005.SN

SWITCH DISCONNECTOR

1600A 3P+SN IP65 600x1000x300mm K6 IK10
EMERGENCY YELLOW/RED SN (SOLID NEUTRAL)

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-HR Series		
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	METAL	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Protection degree IP	IP65		
Type	EMERGENCY	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	YELLOW/RED		
Rated current	1600A	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Poles	3P+SN	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Switch size	K6		
Rated voltage	690V	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Dimensions	600x1000x300mm		
Notes	SN (SOLID NEUTRAL)		
Protection degree IK	IK10		