



590.KGE80005B

SWITCH DISCONNECTOR

800A 3P+N IP65 800x800x300mm K5 IK10
GENERAL GREY/BLACK WITH BUSBAR

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|---|
| Type of product | SWITCH DISCONNECTOR | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Commercial series | ISOLATORS-HR Series | | |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | METAL | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Protection degree IP | IP65 | | |
| Type | GENERAL | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Colour | GREY/BLACK | | |
| Rated current | 800A | EN 60947-1/A2 (2014) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Poles | 3P+N | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Switch size | K5 | | |
| Rated voltage | 690V | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Dimensions | 800x800x300mm | | |
| Notes | WITH BUSBAR | | |
| Protection degree IK | IK10 | | |