



590.GEB12505

SWITCH DISCONNECTOR

125A 3P+N IP55 BS 370x450x180mm KF2 IK08
GENERAL GREY/BLACK FUSE: BS GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SWITCH DISCONNECTOR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Commercial series	ISOLATORS-TP Series		
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	ENGINEERING PLASTIC	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Protection degree IP	IP55	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type	GENERAL		
Colour	GREY/BLACK		
Rated current	125A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	3P+N		
Switch size	KF2		
Fuse type	BS		
Rated voltage	690V		
Dimensions	370x450x180mm		
Notes	FUSE: BS		
GLOW WIRE	GW 650°C		
Protection degree IK	IK08		