



590.HGED8005

SWITCH DISCONNECTOR

80A 3P+N IP65 DIN-NH 315x410x150mm KF1
IK10 GENERAL GREY/BLACK FUSE: DIN-NH

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ISOLATORS-AL Series	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Type of product	SWITCH DISCONNECTOR	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Synthetical description	SWITCH DISCONNECTOR	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	DIE-CAST ALUMINIUM	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Protection degree IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Type	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colour	GREY/BLACK	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	80A		
Poles	3P+N		
Switch size	KF1		
Fuse type	DIN-NH		
Rated voltage	690V		
Dimensions	315x410x150mm		
Notes	FUSE: DIN-NH		
Protection degree IK	IK10		